


# 2SC2240

## NPN Silicon Epitaxial Planar Transistor

for low noise audio amplifier applications.

The transistor is subdivided into two groups, G and L according to its DC current gain

On special request, these transistors can be manufactured in different pin configurations.




1. Emitter 2. Collector 3. Base  
TO-92 Plastic Package

### Absolute Maximum Ratings ( $T_a = 25\text{ }^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Collector Base Voltage	$V_{CBO}$	120	V
Collector Emitter Voltage	$V_{CEO}$	120	V
Emitter Base Voltage	$V_{EBO}$	5	V
Collector Current	$I_C$	100	mA
Base Current	$I_B$	20	mA
Power Dissipation	$P_{tot}$	625	mW
Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	- 55 to + 150	$^\circ\text{C}$

### Characteristics at $T_a = 25\text{ }^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit	
DC Current Gain at $V_{CE} = 6\text{ V}$ , $I_C = 2\text{ mA}$	Current Gain Group G L	$h_{FE}$	200	-	400	-
		$h_{FE}$	350	-	700	-
Collector Base Cutoff Current at $V_{CB} = 120\text{ V}$	$I_{CBO}$	-	-	100	nA	
Emitter Base Cutoff Current at $V_{EB} = 5\text{ V}$	$I_{EBO}$	-	-	100	nA	
Collector Emitter Breakdown Voltage at $I_C = 1\text{ mA}$	$V_{(BR)CEO}$	120	-	-	V	
Collector Emitter Saturation Voltage at $I_C = 10\text{ mA}$ , $I_B = 1\text{ mA}$	$V_{CE(sat)}$	-	-	0.3	V	
Transition Frequency at $V_{CE} = 6\text{ V}$ , $I_C = 1\text{ mA}$	$f_T$	-	100	-	MHz	
Output Capacitance at $V_{CB} = 10\text{ V}$ , $f = 1\text{ MHz}$	$C_{ob}$	-	-	6	pF	










**SEMTECH ELECTRONICS LTD.**



ISO/TS 16949 : 2009 Certificate No. 180713000  
 ISO14001 : 2004 Certificate No. 7116  
 ISO 9001 : 2008 Certificate No. 00719410  
 BS-OHSAS 18001 : 2007 Certificate No. 7116  
 IECQ QC 080000 Certificate No. PRC-18P14-1481

Dated: 08/01/2016 Rev: 02



**SEMTECH ELECTRONICS LTD.**

